

## 6.6 A Current Controlled Halogen - Single End Lamps for Series Operation




### Areas of application

- Airfield Lighting

### Product features and benefits

- Low maintenance costs due to long lamp life
- Consistent light output over the life of the lamp
- Durable construction provides resistance to the effects of vibration
- IR radiation provides guidance in low visibility conditions and facilitates defrosting in cold climates
- FAA approved in conjunction with many OEM fixtures
- Dimmable
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free



Product family datasheet

Technical data

Product description	General Product Information		Electrical Data	Lifetime Data
	ANSI code	LIF code	Nominal wattage	Nominal lifetime
64322	EXL	-	30 W	1500 hr
64311	-	J1/59	36 W	1500 hr
64321	-	J1/57	45 W	1500 hr
64320	EXM	-	45 W	1500 hr
64346	-	J1/58	100 W	1200 hr
64386	-	J1/39	200 W	1500 hr
64350	EVV	-	110 W	1000 hr
58750	EZL	-	200 W	1300 hr
64354	EWR	-	150 W	1500 hr

## Product family datasheet

---

### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

---

### Application advice

For more detailed application information and graphics please see product datasheet.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.