

HBO Microlithography Lamps for ASML i-line Systems




Areas of application

- Microlithography

Product features and benefits

- High spectral intensity with peak irradiance at 365nm wavelength, making it ideal for microlithography
- Designed for long lasting performance
- Qualified with ASML
- Qualified with ASML



Product family datasheet

Technical data

Product description	Electrical Data		Photometric Data	Physical Attributes & Dimensions
	Nominal wattage	Nominal voltage	Light center length (LCL)	Length
HBO 1003 W/PIL	1003 W	27.1 V	85.0 mm ¹⁾	195.0 mm
HBO 1500 W/PIL	1500 W	23 V	118.0 mm ¹⁾	273.0 mm
HBO 2100 W/PIL	2100 W	24 V	118.0 mm ¹⁾	240.0 mm
HBO 2500 W/PIL	2500 W	28.0 V	149.0 mm ¹⁾	340.0 mm
HBO 3500 W/PIL	3500 W	23 V	154.0 mm ¹⁾	360.0 mm

¹⁾ Distance from end of base to tip of anode or cathode (cold)

Product family datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.