

LEDDriving BASIC P21/5W



Product family datasheet

Technical data

Product description	Electrical Data				Photometric Data
	Power input	Nominal voltage	Nominal wattage	Test voltage	Nominal luminous flux
LEDriving BASIC \triangleq P21/5W	1.44 W	12 V	1 W	13.5 V	85/25 lm

Product description	Luminous flux tolerance	Physical Attributes & Dimensions		Lifetime Data	
		Diameter	Diameter	Lifespan B3	Lifespan Tc
LEDriving BASIC \triangleq P21/5W	$\pm 20\%$	20.0 mm	20.0 mm	2000 hr	2000 hr

Product description	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
	Primary article identifier	Candidate list substance 1	CAS No. of substance 1	Safe use instruction
LEDriving BASIC \triangleq P21/5W	4052899463295 4052899414518 4052899414495	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.

Product description	Declaration no. in SCIP database
LEDriving BASIC \triangleq P21/5W	9bf3b981-7442-439c-a86d-e513fc794734 fe6d71fd-c80e-400d-8cc2-14ed29394294 1d480114-7d33-4144-80cc-0d5f7210d25e

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

