

LEDDriving BASIC P21/5W



Product family datasheet

Technical data

	Electrical Data				Photometric Data	
Product description	Power input	Nominal voltage	Nominal wattage		Test voltage	Nominal luminous flux
LEDriving BASIC $\triangleq$ P21/5W	1.44 W	12 V	1 W		13.5 V	85/25 lm
		Physical Attributes & Dimensions	Lifetime Data		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Product description	Luminous flux tolerance		Diameter	Lifespan B3	Lifespan Tc	Primary article identifier
LEDriving BASIC $\triangleq$ P21/5W	$\pm 20\%$	20.0 mm	2000 hr	2000 hr	4052899463295 4052899414518 4052899414495	
Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction		Declaration no. in SCIP database	
LEDriving BASIC $\triangleq$ P21/5W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.		9bf3b981-7442-439c-a86d-e513fc794734 fe6d71fd-c80e-400d-8cc2-14ed29394294 1d480114-7d33-4144-80cc-0d5f7210d25e	

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

