
OSRAM

XENARC COOL BLUE BOOST

Hyper white light for LED look for off-road use





Xenon hyper white light for stylish LED look

Hyper white light due to a special filling system instead of conventional coating



op 10 7,000 11

High contrast and most stylish look



Enhanced brightness

More light allows to see farther and therefore react sooner





Hyper white light with up to 7,000 K for off-road use

XENARC COOL BLUE BOOST features hyper white xenon light for LED look and high color temperatures of up to 7,000 K. This is due to a special filling system instead of conventional coating. The lamps generate enhanced brightness. These products do not have ECE approval. This means they must not be used on public roads in any exterior application. Use on public roads leads to cancellation of operating license and loss of insurance coverage. Several countries do not allow sale and use of these products. Please contact your local distributor for information on the availability in your country.

1) Measured in headlamps

Product family datasheet

Technical data

	Electrical	Electrical Data				Photometric Data
Product description	Power input	Nominal voltage	Nominal wattage	Power input toleranc e	Test voltage	Nominal luminous flux
XENARC COOL BLUE BOOST ≜ D1S	35 W	85 V	35 W	±3 %	13.5 V	3200 lm
XENARC COOL BLUE BOOST ≜ D2S	35 W	85 V	35 W	±3 %	13.5 V	3200 lm
XENARC COOL BLUE BOOST ≜ D3S	35 W	42 V	35 W	±3 %	13.5 V	3200 lm
XENARC COOL BLUE BOOST	35 W	42 V	35 W	±3 %	13.5 V	3200 lm

		Physical Attributes & Dimensions		
Product description	Luminous flux tolerance	Lamp base	Length	Diameter
XENARC COOL BLUE BOOST	±15 %	PK32d-2	83.2 mm	9 mm
XENARC COOL BLUE BOOST	±15 %	P32d-2	77.3 mm	9 mm
XENARC COOL BLUE BOOST	±15 %	PK32d-5	83.2 mm	9 mm
XENARC COOL BLUE BOOST	±15 %	P32d-5	77.3 mm	9 mm

		Lifetime Data		Certificates & standards	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)
Product description	Diameter	Lifespan B3	Lifespan Tc	ECE category	Primary article identifier
XENARC COOL BLUE BOOST ≜ D1S	9 mm	600 hr	1500 hr	_ 1)	4052899439184 4062172404129
XENARC COOL BLUE BOOST ≜ D2S	9 mm	600 hr	1500 hr	_ 1)	4062172404150 4052899441026
XENARC COOL BLUE BOOST ≜ D3S	9 mm	1000 hr	1500 hr	_ 1)	4052899527560 4062172404181
XENARC COOL BLUE BOOST	9 mm	1000 hr	1500 hr	_ 1)	4052899527522

Product description	Candidate list substance 1	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
XENARC COOL BLUE BOOST	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	510b3515-af3b- 4ebb-93d3- c9dd67e73c84 4a196424-fbe4-4fd5- 8eb2-6dfb70acf828

Product family datasheet

Product description	Candidate list substance 1	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
XENARC COOL BLUE BOOST ≜ D2S	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	6c57c564-b94d- 41ad-aafc- 6dd568694c25
XENARC COOL BLUE BOOST ≜ D3S	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	52eaf09b-051b- 4888-b1fc- 0e5b2b78b12f 339d84e0-b5c1- 49b0-814c- 94cae2e6e2fc
XENARC COOL BLUE BOOST	No declarable substances contained			No declarable substances contained

¹⁾ To be operated only with approved electronic control gear

Product family datasheet

Download Data

	File
<u>**</u>	User instruction GPRS_Safety symbols instructions
	ref_pim_amsp_product360degreeimages XENARC COOL BLUE BOOST D1S 66140CBB
	ref_pim_amsp_product360degreeimages XENARC COOL BLUE BOOST OFFROAD D2S 66240CBB
	ref_pim_amsp_product360degreeimages XENARC COOL BLUE BOOST OFFROAD D3S 66340CBB
	ref_pim_amsp_product360degreeimages XENARC COOL BLUE BOOST OFFROAD D4S 66440CBB

Safety advice

XENARC lamp change is recommended to be carried out by a professional. This product must only be operated with approved electronic control gear.

Legal advice

*These products do not have ECE approval. This means they must not be used on public roads in any exterior application. Use on public roads leads to cancellation of operating license and loss of insurance coverage. Several countries do not allow sale and use of these products. Please contact your local distributor for information on the availability in your country.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.















