OSRAM

LEDinspect FLEXIBLE INSPECTION LIGHT





Fully flexible under bonnet inspection light

Place light exactly where you need it, even in tight spaces



Bright light output

Choose between 1000, 400 and 100 lumens output or red light for use at the rear of a vehicle



Long lasting battery life

Experience up to 3 hours (on high), 6.5 hours (on medium) and 20+ hours (on low) battery life. Recharging is easy thanks to the USB-C port.



Versatile fitting options

Features removable elasticated hooks and strong magnetic connections



Inspection lights are a vital part of any professional's toolbox. Under bonnet lamps provide bright light over a wide area to enable professionals to work with maximum visibility.

The LEDinspect FLEXIBLE INSPECTION LIGHT allows users to place light exactly where it is required. Our most versatile inspection light, it features removable elastic straps that allow the light to be fitted to areas as wide as 2.1m. The light strip is fully flexible, allowing the light to bend around the workspace. The rotating ends feature strong magnetic connections and USB-C charging.

Product family datasheet

Technical data

			neral Product ormation				
Product description	Application (obal order Ference	Nom	inal watta	ge	Nominal voltage
INSPECTION LAMP	LED inspecti	on lights LE	EDIL416 1		10 W		5.0 V
	Photometric	Data				Physica Dimens	al Attributes & sions
Product description	Color tempe		Nominal luminous flux		Light color LED		t weight
INSPECTION LAMP	6200-6500 k	(10	00 lm	Whit	nite 259		g
							LED module information
Product description	Length	Wi	dth	Heig	ht		Number of LEDs per module
INSPECTION LAMP	1950 mm	32	.0 mm	39.0	39.0 mm		75
	Lifetime Data	Capabilities	Logistical data	ı	Environn Regulato Informat Informat accordin EU Regul	ory ion ion g Art. 33 lation (E0	C)
Product description	Guarantee	Technology	nology Watt hour per ba		Candidate list substance 1		
INSPECTION LAMP	2 years	LED	8.14		Lead		

Product description	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
INSPECTION LAMP	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	01f2cf81-0802-463c- 8c06-d58936072bea

Product family datasheet

Download Data

File



User instruction
GPRS_Safety symbols instructions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.