


## BATTERYjumpstart 1500



### Starts completely depleted batteries

New Boost function allows user to restart vehicles with depleted batteries



### Powerful Lithium Battery

Starts up to 6-liter petrol and 3-liter diesel vehicles



### PD60W Power Pack

Fast charges phones and other devices via the built in USB ports



### Powerful and safe jumpstarting for 12V vehicles with integrated USB charging and enhanced safety features

The OSRAM BATTERYjumpstart 1500 can jump-start vehicles with engines up to 6L Petrol or 3L Diesel. With 1500A starting power, it is suitable for most 12V cars, vans, SUVs, and LCVs. The boost function enables jump-starting of completely depleted batteries. The unique ergonomic smart clamp connection features longer cables for better accessibility in hard-to-reach areas. Safety features include reverse polarity protection, anti-spike protection, and short circuit protection, with audible and LED indicators. An integrated torch illuminates the work area, and LED indicators show the current battery level. The unit features PD60W fast charge technology for rapid recharging and powerful charging of mobile devices via the USB C and USB A ports.

Product family datasheet

Technical data

|                       | Electrical Data                          | Environmental & Regulatory Information<br>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                        |                                                                                                    |
|-----------------------|------------------------------------------|-----------------------------------------------------------------------------------------------------------------|------------------------|----------------------------------------------------------------------------------------------------|
| Product description   | Boost-Function (start batteries from 0V) | Candidate list substance 1                                                                                      | CAS No. of substance 1 | Safe use instruction                                                                               |
| BATTERYjumpstart 1500 | Yes                                      | Lead                                                                                                            | 7439-92-1              | The identification of the Candidate List substance is sufficient to allow safe use of the article. |

| Product description   | Declaration no. in SCIP database     |
|-----------------------|--------------------------------------|
| BATTERYjumpstart 1500 | 29b37b89-8a00-4a8c-bc7f-646af72bcd86 |

Download Data

| File                                                                              |                                                    |
|-----------------------------------------------------------------------------------|----------------------------------------------------|
|  | Brochures<br>BATTERYjumpstart 1500 Lithium Starter |

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.