

Product family datasheet

LEDguardian TRUCK FLARE Signal TA19 Essential

LEDguardian TRUCK FLARE Signal TA19 Essential



Street legal

Street legal according to §53a StVZO. Use is also permitted in other EU countries 1)



Versatile applications

Mandatory in Germany for vehicles ≥ 3.5t and for vehicles < 3.5t optional and recommended also in other countries



Robust and reliable

Water, dust and shock resistant



Ready for use immediately after purchase

Batteries included in scope of delivery



Light is safety – See and be seen with OSRAM

Our powerful LEDguardian TRUCK FLARE Signal TA19 Essential offers improved visibility and therefore increased safety for you and other road users. With 3 high-performance, long-life LEDs and a bright orange flashing light you can draw attention to yourself by day and night, and preventively alert other road users about a dangerous situation. The warning light is street legal and mandatory in Germany for vehicles ≥ 3.5t according to §53a TA19 StVZO, but it can also be used in other countries and for various vehicle types. ¹¹ lts compact design allows for convenient storage within easy reach in your vehicle. Thanks to its foldout, robust feet, it can be quickly and easily set up next to the warning triangle. In addition, the rubberized standing feet provide non-slip stability, even in wind force 9.

With an operating time of over 15 hours, the LEDguardian TRUCK FLARE Signal TA19 Essential offers long-lasting performance. The integrated test function allows you to check the battery capacity at any time. It is CE and GGVS/ADR certified²⁾, ensuring it meets the safety standards.

With an IP54 and IK06 protection rating, the LED warning light is resistant to the ingress of water and dust as well as insensitive to impacts and shocks. The package includes 4 x AA batteries, making the warning light ready for use immediately after purchase. Additionally, OSRAM provides a 2-year guarantee $^{3)}$ on this product.

Product family datasheet

Technical data

	Product inforn	nation	ion General Product		Electrical Data			
Product description		Application (Category and Product specific)		Global order reference		tage	Nominal voltage	
LEDguardian TA19 Essential	Warning and s lights	afety	LEDSL106		3 W		6.0 V	
	Photometric)ata Phy		ical Attributes & Dimensions			
Product description	Color temperature		Light color LED	Product	Product weight Length		th	
LEDguardian TA19 Essential	2000 K	2000 K Orango		566.00 g 2) mm	
					Lifetime Data	Additio	onal product	
Product description	Width	Width		Height		tee Type of Battery		
LEDguardian TA19 Essential	91.0 mm	91.0 mm 43.0		43.0 mm		Alkalir	ne	
	Capabilities	Certificates & standards		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			of EU	
Product description	Technology	IK Clas	S	Candidate list substance 1		CAS I	No. of substance	
LEDguardian TA19 Essential	LED	IK06		Lead		7439	-92-1	

Product description	Safe use instruction	Declaration no. in SCIP database
LEDguardian TA19 Essential	The identification of the Candidate List substance is sufficient to allow safe use of the article.	2dfb9ae0-4f69-449a- 8593-c11395032197

Product family datasheet

Download Data

File



User instruction

GPRS_Safety symbols instructions



User instruction

LEDguardian TRUCK FLARE Signal TA19 ESSENTIAL

Legal advice

1) Use is also permitted in other EU countries, provided that the respective national regulations are complied with2) Approved in dangerous goods transports according to European Agreement concerning the International Carriage of Dangerous Goods by Road & Dangerous Goods Regulation Road3) For precise conditions please refer to: www.osram.com/am-guaranteeApplication advice:

For more detailed application information and graphics please see product datasheet and user manual.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.