Product family datasheet

# LEDriving SL W21W/5W WHITE

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications Available in Cool White



Replaces conventional W21W/5W lamps Easy upgrade to LED technology with plug & play solutions



OSRAM

Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



#### Suitable LED replacement for W21/5W

LEDriving SL W21W/5W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional W21W/5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

## Product family datasheet

#### Technical data

|                                           | Electrical Data                    |                            |     |                | Photometric Data                |
|-------------------------------------------|------------------------------------|----------------------------|-----|----------------|---------------------------------|
| Product description                       | Power Nominal<br>input             | voltage Nominal w          | -   |                | Nominal luminous<br>flux        |
| LEDriving SL $\doteq$ W21/5W              | 2.7 W 12 V                         | 1 W                        | 13  | .5 V           | 155/25 lm                       |
|                                           | Phys                               | ical Attributes & Dimensic | ons | Lifetime       | Data                            |
| Product description                       | Luminous Dian<br>flux<br>tolerance | neter Diame                | ter | Lifespan<br>B3 | Lifespan<br>Tc                  |
|                                           | toterance                          |                            |     |                |                                 |
| LEDriving SL ≙ W21/5W                     | ±25 % 20.0                         | mm 20.0 n                  | nm  | 1500 hr        | 4000 hr                         |
| LEDriving SL ≙ W21/5W                     | ±25 % 20.0<br>Environmental & Re   |                            |     |                | 4000 hr                         |
| LEDriving SL ≜ W21/5W Product description | ±25 % 20.0<br>Environmental & Re   | gulatory Information       |     | (REACh)        | 4000 hr<br>Safe use instruction |

| Product description              | Declaration no. in<br>SCIP database      |
|----------------------------------|------------------------------------------|
| LEDriving SL $\triangleq$ W21/5W | 4746391f-7cf0-4291-<br>a57a-5bc608210a87 |

\_

### Product family datasheet

#### Download Data

| File                                                      |
|-----------------------------------------------------------|
| User instruction<br>GPRS_Safety symbols instructions      |
| Brochures<br>LEDriving Retrofits - Exchange overview (EN) |

#### Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

#### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.