

LEDriving ERROR CANCELER

Accessories for LED retrofit lamps




Error message free
Bypasses the vehicle's error
detection



Flicker-free
Prevents additional irritating
flashing of the LED lamps



3-year OSRAM Guarantee²⁾





Duopac

Two Error canceler in one box



Convert from halogen to LED with original OSRAM accessories

Some vehicles report a malfunction in the exterior lighting when LED lamps are used. With the new OSRAM LEDriving ERROR CANCELER LED EC02, potential error messages in the on-board system are avoided. These error messages can occur when converting from traditional halogen lamps to LED lamps as these have a lower current consumption than e.g. halogen lamps and thus activate the vehicle's existing error detection mechanism. Furthermore, OSRAM's new and improved LEDriving ERROR CANCELER LED EC02 prevents irritating LED lamp flashing. It is suitable for 12V H7 LED lamps for high and low beam. In addition, OSRAM offers a three-year OSRAM guarantee²⁾ on all accessories in the LEDriving series. Only the combination of OSRAM LED lamps in conjunction with the official OSRAM accessories - LEDriving ADAPTER, LEDriving SMART CANBUS, LEDriving CAPs and LEDriving ERROR CANCELER is approved for the operation of our LED lamps. Details, in particular on the combination of OSRAM accessories and the street-legal NIGHT BREAKER LED and TRUCKSTAR LED lamps, can be found on the respective product pages under: NIGHT BREAKER LED Kompatibilitätslisten | Automotive (osram.de)

Product family datasheet

Technical data

	Electrical Data	Lifetime Data		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Product description	Nominal wattage	Lifespan B3	Lifespan Tc	Primary article identifier	Candidate list substance 1
LEDriving ERROR CANCELER LEDEC02-2HB	1.00 W	2500 hr	2500 hr	4062172383721	Lead

Product description	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
LEDriving ERROR CANCELER LEDEC02-2HB	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	bdd31784-c584- 41b0-b49e- e218e7d29151

Product family datasheet

Download Data

File



User instruction
LEDriving ERROR CANCELER LEDEC02



User instruction GPRS_Safety symbols instructions

Safety advice

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

Legal advice

1) Approved LED light source applies to all vehicle models to specific light functions and further restrictions in the respective country. Must not be used behind red and/or yellow colored glass.

For more details see www.osram.com/nb-led2) For precise conditions please refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.