

## LEDDriving HLT BRIGHT H4

LEDDriving high and low beam lamps for truck



### Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect



### Superior brightness

Up to +300% compared to minimum ECE R112. More light allows to see farther and therefore react sooner. Signs, obstacles and hazards can be recognized sooner



### LED replacement for conventional H4 high and low beam lamps

Reduced glaring thanks to an optimized light distribution



### H4 LED replacement for 24V

LEDDriving HLT BRIGHT replacement lamps offer a modern and intense light with a color temperature of up to 6,000 Kelvin. These replacement lamps are suitable for conventional H4 high and low beam lamps. LEDDriving HLT BRIGHT for high and low beam off-road applications are 24 V compatible and stand out with superior brightness, high compatibility, easier installation due to integrated driver and no radio disturbance. The pair of lamps comes with a 4-year OSRAM guarantee. For precise guarantee conditions please refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee). These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| Product description                  | Electrical Data |                 |                 |                       |              | Photometric Data      |
|--------------------------------------|-----------------|-----------------|-----------------|-----------------------|--------------|-----------------------|
|                                      | Power input     | Nominal voltage | Nominal wattage | Power input tolerance | Test voltage | Nominal luminous flux |
| LEDriving HLT BRIGHT $\triangleq$ H4 | 15/15 W         | 24 V            | 15 W            | $\pm 20\%$            | 28.0 V       | 1200/1500 lm          |

| Product description                  | Luminous flux tolerance | Physical Attributes & Dimensions |         |          |
|--------------------------------------|-------------------------|----------------------------------|---------|----------|
|                                      |                         | Lamp base                        | Length  | Diameter |
| LEDriving HLT BRIGHT $\triangleq$ H4 | $\pm 20\%$              | P43t                             | 80.2 mm | 14.0 mm  |

| Product description                  | Lifetime Data | Environmental & Regulatory Information<br>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                            |                        |
|--------------------------------------|---------------|-----------------------------------------------------------------------------------------------------------------|----------------------------|------------------------|
|                                      | Lifespan Tc   | Primary article identifier                                                                                      | Candidate list substance 1 | CAS No. of substance 1 |
| LEDriving HLT BRIGHT $\triangleq$ H4 | 2000 hr       | 4062172379779                                                                                                   | Lead                       | 7439-92-1              |

| Product description                  | Safe use instruction                                                                               | Declaration no. in SCIP database     |
|--------------------------------------|----------------------------------------------------------------------------------------------------|--------------------------------------|
| LEDriving HLT BRIGHT $\triangleq$ H4 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 9ed29aa3-108c-4e27-8fdb-3c4fb5974281 |

Download Data

| File                                                                              |                                                           |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------|
|  | User instruction<br>LEDriving HLT BRIGHT                  |
|  | User instruction<br>GPRS_Safety symbols instructions      |
|  | Brochures<br>LEDriving Retrofits - Exchange overview (EN) |

Safety advice

Application advice:For more detailed application information and graphics please see product datasheet and user manual.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.